



INVERTER ARC™ 230

DC INVERTER STICK WELDER

Recommended Welding Thickness

18 Ga. to 5/16"

10-155A DC 230V/1Ph/60Hz

Unit Includes:

- 10 ft. Work cable with small dins connector and clamp
- 10 ft. Electrode holder with small dins connector
- Shoulder strap for portability
- Instruction manual
- 6 ft. Input cable with attached 50 amp (NEMA 6-50P) plug
- One-year warranty parts and labor



Includes



USE THESE ELECTRODES WITH THIS WELDER

| Dia. | In. | 5/64 | 3/32 | 1/8 | 5/32 |
|-------|------|-------|-------|-------|-------|
| | (mm) | (2.0) | (2.4) | (3.2) | (4.0) |
| E6013 | | ● | ● | ● | |
| E6011 | | | ● | ● | ● |
| E7018 | | | ● | ● | |

| PART NO | MODEL NO. | INPUT POWER | RATED DC OUTPUT | WELDING OUTPUT RANGE | WEIGHT | DIMENSIONS (in.) |
|---------|-------------------|-------------|--------------------------|----------------------|--------|------------------|
| K2790-1 | Inverter Arc® 230 | 230/1/60 | 150A Ⓢ 30% Duty Cycle | 10-155A DC | 22 LBS | 12 x 6.5 x 14.6 |